

# *Inertia 860 Setup Instructions*

## **Operating instructions**

It is necessary for you to follow these following steps in specified order to successfully install your new Inertia 860.

1. Connect Inertia 860 to the receiver. **Do not** connect the servo to the Inertia 860 at this time.
2. Assign gyro gain to a 2 position switch to facilitate switching between Normal and ACVS.
3. Ensure that the transmitter trims and sub-trims are set to zero and that collective pitch to tail pitch mixing is disabled. Power on the Inertia 860 and check that the LED responds when toggling the gain switch. When the LED is on it is AVCS mode and off for Normal mode.
4. Refer to the following LCD Setting Adaptor guide for detailed setting.
5. Connect the servo to the Inertia 860.
6. In Normal mode perform mechanical adjustment of the servo horn and control linkages to achieve approximately 8deg tail pitch.
7. Adjust gyro gain for both Normal and AVCS modes via your transmitter.
8. Perform final checks. Confirm correct relationship of rudder stick and gyro response to tail movement. Confirm that there is no mechanical binding.

## **Power On :**

Once power on, LCD will display HELLO. After 5 seconds, configuration card will display gyro settings and is ready for use.

**Default Setting :** When HELLO is display, press **+10** and **-1** buttons simultaneously. Configuration will return to default value.

**System Reset :** Reset button is located at the bottom of LCD configuration card.

## **Button Description :**

Total 7 function keys: FUNC+, FUNC-, +10, -10, +1, -1, Reset

Description	Function
FUNC+, FUNC-	Scroll up/down function menu
+10, -10	Increase (+) or decrease (-) value by 10 units each time.  Automatically change to 1 units if the maximum function value is less than 20.
+1, -1	Increase (+) or decrease (-) value by 1 unit each time.
Reset	System reset

**Detailed settings of Function Menu:**

<b>1、SERVOTYP</b>	
<b>servo type selection</b>	
Menu Items	Description
152-33 (Default)	<p><b>Servo pulse width 1520us, working frequency 333Hz includes :</b></p> <p>Futaba : S9253、S9254、S9650、S9257、S3153</p> <p>JR :</p> <p>8900G</p> <p>、DS3405、DS3500</p> <p>Hitec : HS-5084MG、HS-5925MG</p> <p>Align : DS510、DS520、DS610、DS620</p> <p>LogicTech :</p> <p>3100G</p> <p>Most digital servo without special marking should be in this category.</p>
76-33	<p><b>Servo pulse width 760us, working frequency 333Hz includes :</b></p> <p>Futaba : S9251、S9256、BLS251</p> <p>LogicTech :</p> <p>6100G</p>
152-25	<p><b>Servo pulse width 1520us, working frequency 250Hz includes :</b></p> <p>Futaba : S3154</p> <p>JR :</p> <p>8700G</p> <p>、</p> <p>2700G</p>

## 2、GYDIRECT

### Gyro direction selection

Direction of resulting yaw.

Direction of resulting yaw

Attention: Check that the rudder direction matches the transmitter stick direction. Otherwise, please reverse the rubber servo direction in transmitter program.

Menu items	Description
NORM (Default)	Rotate the helicopter left (nose). Rudder servo should compensate to the right automatically. Otherwise, change value to "REV". As shown in the diagram
REV	Rotate the helicopter left (nose). Rudder servo should compensate to the right automatically. Otherwise, change value to "NORM". As shown in the diagram.

## 3、MID-TRIM

### Rudder Servo Neutral Adjustment

Attention: Rudder SUB TRIM value of Transmitter should be set to zero . Install rudder servo horn to closest to 90 degree. Use MID-TRIM to fine tune the neutral point of servo horn to achieve exact 90 degree. Check the neutral position by switching the Inertia 860 to the NOR mode, or by moving the rudder stick to the left and right at least three times at high speed and immediately returning the stick to the neutral position. This temporarily resets the rudder servo.

Menu items	Description
-100 ~ 0 ~ +100 (Default 0)	Fine tune rudder servo neutral point.

#### 4、 L-LIMIT

##### Rudder Left Pitch Travel Limit

Menu items	Description
0 ~ 240  (Default 160)	Adjust rudder servo travel at end limit.
Suggestion	Suggested setting between 160~230. If setting is higher than 230, please install ball link to the outer hole of servo horn or use longer horns. If setting is lower than 160, please install ball link to the inner hole of servo horn or use shorter horns. It is recommended to keep difference between L-LIMIT and R-LIMIT within $\pm 20$ .

#### 5、 R-LIMIT

##### Rudder Right Pitch Travel Limit

Menu items	Description
0 ~ 240  (Default 160)	Adjust rudder servo travel at end limit.
Suggestion	Suggested setting between 160~230. If setting is higher than 230, please install ball link to the outer hole of servo horn or use longer horns. If setting is lower than 160, please install ball link to the inner hole of servo horn or use shorter horns. It is recommended to keep difference between R-LIMIT and L-LIMIT within $\pm 20$ .

#### 6、 RPIRGAIN

##### Right Piro Stop Gain

Menu items	Description
50 ~ 200  (Default 100)	The higher the setting, the harder the braking effect in piro stops.  The lower the setting, the softer the braking effect in piro stops.
Suggestion	If tail bounce back occurs, please lower the setting . Excess hard braking for piro stop will affect the service life of rudder servo!

#### 7、 LPIRGAIN

##### Left Piro Stop Gain

Menu items	Description
50 ~ 200  (Default 100)	The higher the setting, the harder the braking effect in piro stop .  The lower the setting, the softer the braking effect in piro stop .
Suggestion	If tail bounce back occurs, please lower the setting . Excess hard braking for piro stop will affect the service life of rudder servo!

## 8、 RUD-GAIN

### Rudder Stick Gain

Menu items	Description
50 ~ 150  (Default 100)	Fine tune the stick response to the actual piro rate. The higher the setting, the more sensitive the stick movement.

## 9、 ACC-EXP

### Acceleration Curve

Menu items	Description
0 ~ 15  (Default 0)	The higher the value, the smoother and longer it takes to reach piro speed from static.

## 10、 DEC-EXP

### Deceleration Curve

Menu items	Description
0 ~ 15  (Default 0)	The higher the value, the longer it takes for the tail to slow down. Used to smoothen the deceleration of piro when coming to a stop.

## 11、 DEADBAND

Menu items	Description
5 ~ 100  (Default 5)	Rudder has no response if stick movement in deadband zone.  Useful to prevent minor unintentional rudder stick commands.

## 12、 N-RUDEXP

### Normal Rudder Curve

Menu items	Description
-100 ~ +100  (Default 0)	Normal Gyro expo curve to the stick movement in non-head lock mode

### 13、 A-RUDEXP

#### AVCS Rudder Curve

Menu items	Description
-100 ~ +100  (Default 0)	AVCS Gyro expo curve to the stick movement in head lock mode

#### Gyro activation auto-check

When you power on the Inertia 860 it will immediately perform automatic calibration of the rudder stick and gyro natural points. During this time the helicopter must remain undisturbed and the rudder stick must be left at the neutral point. The calibration lasts approximately 3 seconds and upon completion the tail servo will move to the middle. The calibration will not start if the Inertia 860 is not receiving a valid rudder signal from the receiver or if the rudder stick is not centered. In both cases the LED will emit the Error flashing sequence (see Status LED section later in this instruction).

#### Status LED

During normal operation the LED provides simple status information for users.

On :	AVCS mode. Stick at neutral.
Short blink three times:	AVCS mode. Rudder input detected.
Off :	Normal mode.
repeating flash:	Error. Gyro not receiving valid signal from the receiver or unable to calibrate because the rudder stick is not centered.

If you require further assistance please email us at [help@inertiarc.com](mailto:help@inertiarc.com)

#### Our Business

Very simple, we want you to be happy with the products that you purchase.

We will give A+ customer service and make every effort to keep you flying and happy as quick as possible.



**Inertia 860 AT WORK**